



HIGH LUMEN VAPOR TIGHT

C151-LED-S Series

- IP65 Waterproof
- High lumen output
- Aluminum heat sink

Optional:

- Dimmable
- Microwave motion sensor
- Emergency battery pack

Specification:

Input Voltage	100-277V AC
Frequency	50/60Hz
CRI	≥80Ra
Power Factor	≥0.95
THD	≤13%
LED Type	Epistar 2835
Luminous Efficiency	≥85
Ambient Temp.	-20°C~40°C
LED lifespan	50,000 hours
Warranty	5 years

Construction:

- IP65 waterproof
- PC housing body and lens
- Stainless steel mounting brackets
- Stainless steel clips
- Isolated LED driver
- 1.2mm Aluminum heat sink
- LED strips can be pulled to replace

Application:



Parking Garages



Warehouse

Model	Watt.	Size	Size(mm)	Lumens	Function	Cert.
C151-LED420-S	80W	4'	1270x134x94	7600-8800lm		ETL
C151-LED430-S	120W	4'	1270x134x94	11400-13200lm		ETL, DLC
C151-LED420-S-D	80W	4'	1270x134x94	7600-8800lm	Dimming	ETL
C151-LED430-S-D	120W	4'	1270x134x94	11400-13200lm	Dimming	ETL, DLC

- CCT: 3000/4000/4500/5000/6000K