



Flood light Series

C240-F41 SERIES

Lifespan 50,000hrs
 Ambient Temperature -40°C~+40°C
 Humidity $\leq 95\%$

FEATURES

- ▶ High pressure die cast aluminum housing, Anti-static powder coat finish.
- ▶ Highly efficient thermal conductive heat dissipation system.
- ▶ High efficient Cree X-TE LED Chip module ensures excellent performance.
- ▶ The fixture installation angle allow easy installation and maintenance.
- ▶ IP Rating: IP66 (Module)

APPLICATIONS

- ▶ Gymnasiums, Billboards, Buildings, Parks, Parking Lots, etc.

CERTIFICATION



LM-79 LM-80



One Light More Allication

SPECIFICATIONS

Input Power	ETL	DLC	Input Voltage	CCT	CRI	Delivered Lumens(5K)	Power Factor	THD	Installation
F41-20W	YES	YES	100-277V 50/60HZ	2700- 6500K	>75	1,900 LM	>0.92	<15%	Slip Fitter
F41-30W	YES	YES				2,600 LM			

More models and wattages will be DLC listed, with time.

DIMENSION

Inch(mm)

Model	Input Power	WEIGHT (Kg)
F41A	20W	1.2
	30W	1.3

Distribution Curve Flux

