


24W/32W LED 120V

- 30 000 hours (L70/B50)
- Not dimmable
- 3000K
- CRI>80
- MacAdam/SDCM: 3
- Fixed LED Light Source. Can be replaced by authorized personnel.

2000 LED

- 50 000 hours (L70/B50)
- Not dimmable
- 3000K (4000K on request)
- CRI>80
- MacAdam/SDCM: 3
- Fixed LED Light Source. Can be replaced by authorized personnel.

Photometric: 2x18W



Materials and Manufacturing:

The aluminium housing is made of high purity marine grade aluminium and treated with a 6 stage chrome plating treatment and dry powder polyester coating ensuring excellent corrosion resistance.

All screws are made of marine grade stainless steel. The diffuser is made of UV stabilized polycarbonate protecting against warping or discoloration and is vandal proof.



	2x18W G24d-2 230V	2x18W HF G24q-2 230V	2x26W G24d-3 230V	2x26W HF G24q-3 230V
WHITE	611881	611882	611883	611886
BLACK	614881	614882	614883	614886
GRAPHITE	623881	623882	623883	623886

	2000 LED 3000K Fixed LED Light Source, 230V	24W LED 3000K 120V ETL Fixed LED Light Source, 120V	32W LED 3000K 120V ETL Fixed LED Light Source, 120V
WHITE	621886	641882	641883
BLACK	624886	644882	644883
GRAPHITE	633886	643882	643883



MATERIAL: Housing: Aluminium. Surface treatment: Dry powder polyester coating. Diffuser: UV-stabilized polycarbonate

