

18W LED 120V




- 30 000 hours (L70/B50)
- Not dimmable
- 3000K
- CRI>80
- MacAdam/SDCM: 3
- Fixed LED Light Source. Can be replaced by authorized personnel.

1100 LED

- 50 000 hours (L70/B50)
- 840 lm (3000K)
- Not dimmable
- 3000K
- CRI>80
- MacAdam/SDCM: 3
- Fixed LED Light Source. Can be replaced by authorized personnel.

Photometric: 1100 LED




PRIMO LED SENSOR

Page: 159




PRIMO	E26 ETL E26 120V IP65	E27 E27 230V IP65	18W G24d-2 230V IP65	18W HF G24q-2 230V IP65	26W G24d-3 230V IP65
WHITE	651578	611570	611572	611573	611574
BLACK	654578	614570	614572	614573	614574
GRAPHITE	653578	623570	623572	623573	623574
RECESSING PLATE	900114	900114	900114	900114	900114
	26W HF G24q-3 230V IP65	1100 LED 3000K Fixed LED, 230V IP65	1100 LED 3000K TWILIGHT Fixed LED, 230V IP65	18W LED 3000K 120V ETL Fixed LED Light Source, 120V	
WHITE	611575	641570	641574	621575	
BLACK	614575	644570	644574	624575	
GRAPHITE	623575	643570	643574	633575	
RECESSING PLATE	900114	900114	900114	900114	

MATERIAL: Housing: Aluminium. Surface treatment: Dry powder polyester coating. Diffuser: UV-stabilized polycarbonate



Recessing plate



This fixture is also available with a back plate allowing the fixture to be semi recessed into concrete walls or other types of construction material.

No recessing plate



W/recessing plate



Materials and Manufacturing:

The aluminium housing is made of high purity marine grade aluminium and treated with a 6 stage chrome plating treatment and dry powder polyester coating ensuring excellent corrosion resistance.

All screws are made of marine grade stainless steel. The diffuser is made of UV stabilized polycarbonate protecting against warping or discoloration and is vandal proof.