




18W LED 120V

- 30 000 hours (L70/B50)
- Not dimmable
- 3000K
- CRI>80
- MacAdam/SDCM: 3
- Fixed LED Light Source. Can be replaced by authorized personnel.

1100 LED

- 50 000 hours (L70/B50)
- 610 lm (3000K)
- Not dimmable
- 3000K
- CRI>80
- MacAdam/SDCM: 3
- Fixed LED Light Source. Can be replaced by authorized personnel.


Photometric: 1100 LED



SOLO	E26 ETL E26 120V IP65	E27 E27 230V IP65	18W G24d-2 230V IP65	18W HF G24q-2 230V IP65	26W G24d-3 230V IP65
WHITE	651558	611550	611552	611553	611554
BLACK	654558	614550	614552	614553	614554
GRAPHITE	653558	623550	623552	623553	623554
RECESSING PLATE	900114	900114	900114	900114	900114

	26W HF G24q-3 230V IP65	1100 LED 3000K Fixed LED, 230V IP65	1100 LED 3000K TWILIGHT Fixed LED, 230V IP65	18W LED 3000K 120V ETL Fixed LED Light Source, 120V
WHITE	611555	641550	641554	621555
BLACK	614555	644550	644554	624555
GRAPHITE	623555	643550	643554	633555
RECESSING PLATE	900114	900114	900114	900114

MATERIAL: Housing: Aluminium. Surface treatment: Dry powder polyester coating. Diffuser: UV-stabilized polycarbonate




Recessing plate

This fixture is also available with a back plate allowing the fixture to be semi recessed into concrete walls or other types of construction material.

No recessing plate



W/recessing plate



Materials and Manufacturing:

The aluminium housing is made of high purity marine grade aluminium and treated with a 6 stage chrome plating treatment and dry powder polyester coating ensuring excellent corrosion resistance.

All screws are made of marine grade stainless steel. The diffuser is made of UV stabilized polycarbonate protecting against warping or discoloration and is vandal proof.