




18W LED 120V

- 30 000 hours (L70/B50)
- Not dimmable
- 3000K
- CRI>80
- MacAdam/SDCM: 3
- Fixed LED Light Source. Can be replaced by authorized personnel.

1100 LED


- 50 000 hours (L70/B50)
- 440 lm (3000K)
- Not dimmable
- 3000K
- CRI>80
- MacAdam/SDCM: 3
- Fixed LED Light Source. Can be replaced by authorized personnel.

Photometric: 1100 LED



UNO	E26 ETL E26 120V IP65	E27 E27 230V IP65	18W G24d-2 230V IP65	18W HF G24q-2 230V IP65	26W G24d-3 230V IP65
WHITE	651648	611640	611642	611643	611644
BLACK	654648	614640	614642	614643	614644
GRAPHITE	653648	623640	623642	623643	623644
RECESSING PLATE	900114	900114	900114	900114	900114
	26W HF G24q-3 230V IP65	1100 LED 3000K Fixed LED, 230V IP65	1100 LED 3000K TWILIGHT Fixed LED, 230V IP65	18W LED 3000K 120V ETL Fixed LED Light Source, 120V	
WHITE	611646	641640	641644	621645	
BLACK	614646	644640	644644	624645	
GRAPHITE	623646	643640	643644	633645	
RECESSING PLATE	900114	900114	900114	900114	

MATERIAL: Housing: Aluminium. Surface treatment: Dry powder polyester coating. Diffuser: UV-stabilized polycarbonate



Recessing plate


This fixture is also available with a back plate allowing the fixture to be semi recessed into concrete walls or other types of construction material.



No recessing plate



W/recessing plate



Materials and Manufacturing:

The aluminium housing is made of high purity marine grade aluminium and treated with a 6 stage chrome plating treatment and dry powder polyester coating ensuring excellent corrosion resistance.

All screws are made of marine grade stainless steel. The diffuser is made of UV stabilized polycarbonate protecting against warping or discoloration and is vandal proof.

